






Project/Equipment		sTGC Wire Cable for QL2	
Document		Designer	Alam Toro
		Drawn by	Alam Toro
		Check by	-
		Last Mod.	-
		File	wCable_QL2.SchDoc
		Print Date	22/12/2017 15:28:59
sTGC Wire Cable for QL2 Main Sheet		Sheet	1 of 1
		Size	A4
European Organization for Nuclear Research CH-1211 Genève 23 - Switzerland		Rev	1.0



Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					





Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					




Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					



Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					




Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					



sTGC_uCable_0L2:
u2HB Side

sTGC_uCable_0L2:
pAB Side



Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					





A nSYB 2iqe
W z10C~nCsp1e~0rS:

A bYB 2iqe
z10C~nCsp1e~0rS:



Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					





Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					




Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					




Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					




Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					




Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					







Symbol	Hit Count	Finished Hole Size	Plated	Hole Type
⊗	4	78.74mil (2.000mm)	PTH	Round
□	120	7.87mil (0.200mm)	PTH	Round
	124 Total			



Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					



Layer	Name	Material	Thickness	Constant	Hard Stack	Flex Stack
1	Top Overlay					
2	Top Solder	Solder Resist	0.010mm	3.5		
3	L1	Copper	0.035mm			
4	Dielectric 1	FR-4	0.650mm	4.2		
5	L2	Copper	0.035mm			
6	Dielectric 2	Flex	0.150mm	4.2		
7	L3	Copper	0.035mm			
8	Dielectric 3	FR-4	0.650mm	4.2		
9	L4	Copper	0.035mm			
10	Bottom Solder	Solder Resist	0.010mm	3.5		
11	Bottom Overlay					



A nSYB 2iqe
W zLGC~nCspIe~0rS:

A bYB 2iqe
zLGC~nCspIe~0rS:

Comment	Description	Designator	Footprint	LibRef	Quantity
ERM8-040-01-L-D-EM2-L		P1, P2	ERM8-040-01-L-D-EM2-L	ERM8-040-01-L-D-EM2-L	2